

Specifications

Trimble SPS985 GNSS Smart Antenna

Provided by Xpert Survey Equipment
[Click Trimble SPS985 for Product Info and Updated Pricing](#)



Receiver Name

SPS985 GNSS Smart Antenna

Configuration Option

Base and Rover interchangeability
 Rover position update rate
 Rover maximum range from base radio
 Rover operation within a VRS™ network
 Heading and Moving Base operation
 Factory options

Yes, upgradeable to Rover, Base or Rover / Base
 1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz
 Unrestricted, typical range 2–5 km (1.2–3 miles) without radio repeater
 Yes
 Yes - option⁷
 See Receiver Upgrades below

General

Keyboard and display

LED indicators for satellite tracking, radio link status, WiFi and power
 On/Off key for one-button startup
 N/A
 N/A

Dimensions (L × W × D)

12 cm (4.7 in) × 13 cm (5.1 in) including connectors

Weight

1.55 kg (3.42 lb) receiver only including radio and battery
 Complete system (rover including controller and pole) 3.9 kg (8.6 lbs)

Antenna Options

GA510
 GA530
 GA810

 L1/Beacon, DSM 232
 Zephyr™ Model 2
 Zephyr Geodetic™ Model 2
 Zephyr Model 2 Rugged
 Zephyr, Zephyr Geodetic, Z-Plus, Micro-Centered™

NA, inbuilt
 N/A
 N/A

 N/A
 N/A
 N/A
 N/A
 N/A

Temperature

Operating¹
 Storage
 Humidity
 Waterproof

–40 °C to +65 °C (–40 °F to +149 °F)
 –40 °C to +75 °C (–40 °F to +167 °F)
 100%, condensing
 IP67 for submersion to depth of 1 m (3.3 ft), dustproof

Shock and Vibration

Pole drop
 Shock – Non-operating
 Shock – Operating
 Vibration

Designed to survive a 2 m (6.6 ft) pole drop onto concrete
 To 115 G, 6msec
 To 60 g, 10msec, half-sine
 Mil-Std-810G, FIG 514.6D-I, Mil-Std-202G, FIG 214-I, Condition D

Specifications

Trimble SPS985 GNSS Smart Antenna

Measurements

Advanced Trimble Maxwell™ 6 Custom GNSS chips
High-precision multiple correlator for GNSS pseudorange measurements
Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low-time domain correlation, and high-dynamic response
Very low noise carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
Trimble EVEREST™ multipath signal rejection
L-Band: OmniSTAR VBS, HP, XP, G2 by subscription
GPS L1 C/A, L2C, L2E (Trimble method for tracking unencrypted L2P) upgradable to L5. 440 channels
Upgradeable to GLONASS L1/L2C/A, L1/L2P Full Cycle Carrier
Upgradeable to Galileo: L1 CBOC, E5A, E5B & E5AltBOC⁸
Upgradeable to Compass: B1, B2, B3
4-channel SBAS L1 C/A, L5 (WAAS/EGNOS/MSAS)
QZSS: L1 C/A, L1C, L1 SAIF, L2C, L5

SBAS (WAAS/EGNOS/MSAS) Positioning³

Accuracy

Better than 5 m 3DRMS (16 ft)

Code Differential GPS Positioning²

Horizontal accuracy

0.25 m + 1 ppm RMS (0.8 ft + 1 ppm RMS)

Vertical accuracy

0.50 m + 1 ppm RMS (1.6 ft + 1 ppm RMS)

OmniSTAR Positioning

VBS service accuracy

Horizontal <1 m (3.3 ft)

XP service accuracy

Horizontal 0.2 m (0.66 ft), Vertical 0.3 m (1.0 ft)

HP service accuracy

Horizontal 0.1 m (0.33 ft), Vertical 0.15 m (0.5 ft)

Location RTK Positioning

Horizontal accuracy

Location RTK (10/10) or (10/2) 10 cm + 1 ppm RMS (0.32 ft + 1 ppm)

Vertical accuracy

Location RTK (10/10) 10 cm + 1 ppm RMS (0.32 ft + 1 ppm)

Location RTK (10/2) 2 cm + 1 ppm RMS (0.065 ft + 1 ppm)

Real-Time Kinematic (RTK up to 30 km)

Positioning²

Horizontal accuracy

8 mm + 1 ppm RMS (0.026 ft + 1 ppm RMS)

Vertical accuracy

15 mm + 1 ppm RMS (0.05 ft + 1 ppm RMS)

Trimble VRS⁹

Horizontal accuracy

8 mm + 0.5 ppm RMS (0.026 ft + 0.5 ppm)

Vertical accuracy

15 mm + 0.5 ppm RMS (0.05 ft + 0.5 ppm)

Precise Heading

Heading accuracy

When combined with SPS985⁷

2 m antenna separation

0.09° RMS

10 m antenna separation

0.05° RMS

Initialization Time

Regular RTK operation with base station

Single/Multi-base

typically less than 8 seconds

Initialization reliability⁴

>99.9%

Power

Internal

Rechargeable, removable 7.4 V, 2.6 Ah Lithium-ion battery in internal battery compartment

Internal battery operates as a UPS during an ext power source failure

Internal battery will charge from external power source as long as source can support the power drain

Integrated charging circuitry

Specifications

Trimble SPS985 GNSS Smart Antenna

Power

External

External power input with over-voltage protection on Port 1 (7-pin Lemo 2-key).
Minimum 10.8 V, shutdown optimized for 12V lead acid battery operation

Power source supply (Internal/External) is hot-swap capable in the event of
power source removal or cut off

DC external power input with over-voltage protection on Port 1 (Lemo)
Receiver automatically turns on when connected to external power
N/A

Power over Ethernet (PoE)

Power consumption

3.7 W in rover mode with internal receive radio
5.2 W in base mode with internal 0.5 W transmit radio

Operation Time on Internal Battery

Rover

4.6 hours; varies with temperature

Base station

450 MHz systems

Approximately 3.5 hours; varies with temperature⁵

900 MHz systems

Approximately 3.5 hours; varies with temperature

Regulatory Approvals

FCC Part 15 Subpart B (Class B Device), Part 15.247, Part 90
Canadian ICES-003. Cet appareil numérique de la classe B est conforme à la
norme NMB-003 du Canada.

Canadian RSS-310, RSS-210, and RSS-119.
Cet appareil est conforme à la norme CNR-310, CNR-210, et
CNR-119 du Canada.

CE mark compliance
C-tick mark compliance
Japan MIC

RoHS compliant
WEEE compliant

Communications

Lemo (Serial)

7-pin Lemo 2-key, Power Input, USB

Modem 1 (Serial)

N/A

Modem 2 (Serial)

N/A

1PPS (1 Pulse-per-second)

N/A

Ethernet

N/A

WiFi

Client or Access Point. Receive or transmit corrections

Bluetooth wireless technology

Fully-integrated, fully-sealed 2.4 GHz Bluetooth module⁶

Integrated radios (optional)

Fully-integrated, fully-sealed internal 410-470 MHz Tx/Rx; Internal 900 MHz
Tx/Rx

Channel spacing (450 MHz)

12.5 kHz or 25 kHz spacing available

Sensitivity (450 MHz)

-114 dBm (12 dB SINAD)

450 MHz output power

0.5 W, upgradeable to 2W

900 MHz output power

1.0 W

Frequency approvals (902-928 MHz)

USA/Canada

External GSM/GPRS, cell phone support

Supported for direct-dial and Internet-based correction streams using the
SCS900 software

Cell phone or GSM/GPRS modem inside controller

Internal MSK Beacon receiver

N/A

Receiver position update rate

1 Hz, 2 Hz, 5 Hz, 10 Hz, and 20 Hz positioning

Correction data input

CMR™, CMR+™, CMRx™, RTCM 2.x, RTCM 3 (require Rover upgrade)

Correction data output

CMR, CMR+, CMRx, RTCM 2.x, RTCM 3 (require Base upgrade)

Data outputs

NMEA, GSOF

Receiver Upgrades

Location RTK (10/2), (10/10), or (30/30)

Precision RTK Rover, Base or Rover/Base

L5, GLONASS, GALILEO, Compass GNSS¹⁰

1 GB Internal Data Logging. Moving Base and Heading

2 Watt upgrade for 450 MHz radio

Notes

1 Receiver will operate normally to those temperature limits. Internal batteries will operate from -20 °C to +48 °C

2 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended survey practices.

3 Depends on SBAS system performance.

4 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.

5 If your receiver has the 2.0 W upgrade, you will experience reduced battery performance compared to the 0.5 W solution.

6 Bluetooth type approvals are country specific. For more information, contact your local Trimble office or representative.

7 When receiver is combined with an SPS985 with Moving Base installed or other suitable SPS receivers.

8 Galileo Commercial Authorization

Developed under a Licence of the European Union and the European Space Agency.

9 Networked RTK PPM values are referenced to the closest physical base station

10 This Trimble SPS Receiver is capable of supporting existing and planned GNSS satellite signals, including GPS, GLONASS, GALILEO, Compass and QZZ, and existing and planned augmentations to these GNSS systems.

Specifications

Trimble SPS985 GNSS Smart Antenna

Specifications subject to change without notice.

© 2012, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and TSC3 are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. CMR, CMR+, CMRx, EVEREST, Maxwell, and VRS are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners.

Trimble Heavy Civil Construction Business Area

5475 Kellenburger Road
Dayton, Ohio 45424
USA
800-538-7800 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner