

Provided by Xpert Survey Equipment  
[Click Trimble SPS551H for Product Info and Updated Pricing](#)

### KEY FEATURES

- Rugged, weatherproof modular receiver design
- GPS L1/L2, SBAS and OmniSTAR VBS/XP/HP capable
- Keypad and display for easy configuration and status monitoring
- Bluetooth®, Ethernet, Serial, and USB communications
- Integrated battery that also acts as a UPS power supply
- Optional integrated 450M Hz UHF or 900 MHz radios for easy configuration
- Industry standard NMEA, RTCM, and CMR™ inputs and outputs
- 1PPS output for time synchronization with other devices
- Upgrades available to track GPS L2C and GLONASS

### SPS551H HEADING ADD-ON RECEIVER FEATURES

- Provides precise heading capability when combined with any SPSx51 receiver
- Upgrade available to track L2C and GLONASS

### FLEXIBLE GPS RECEIVERS FOR LOCATION GPS POSITIONING IN LAND AND MARINE ENVIRONMENTS

The Trimble® SPS551 Modular GPS receiver provides a range of Location GPS<sup>1</sup> positioning techniques ideal for system integrators, OEMs, and land or marine contractors who require real-time positions. The Trimble SPS551 receiver can also be combined with either the Trimble SCS900 Site Controller Software for land-based rover applications or Trimble HYDROpro™ software for marine positioning solutions.

The SPS551 receiver can operate in all Location GPS modes, including operation with Satellite Based Augmentation Systems (SBAS), Differential GPS (DGPS), OmniSTAR (VBS, XP, and HP services), and Location RTK mode for decimeter level positioning. When combined with the Trimble SPS551H Heading Add-on receiver, the SPS551 receiver delivers both Location GPS position and precise GPS heading capabilities suitable for rapid real time positioning and orientation of vessels, barges and vehicles.

#### Location RTK Accuracy to 10 Centimeters

Location RTK mode delivers a horizontal and vertical positioning accuracy of 10 cm. Location RTK operations can be accomplished using CMR+™ correction outputs from any available Trimble RTK (Real-time Kinematic) base, CORS station or Trimble VRS™ network through radio, cell phone, or an Internet connection.

For DGPS and Location RTK operations, the receiver can be used with an external radio modem, or be equipped with either a 450 MHz (UHF) or 900 MHz internal radio capable of both transmit and receive operations.

#### Flexible Options to Suit Changing Job Site Requirements

Modularity provides the flexibility to mount the receiver and GPS antenna in a variety of ways, allowing for operation on a pole, backpack, site vehicle, on light machinery, or on a marine vessel. The receiver can be mounted in an accessible location where it is easy to configure and is secure from theft and from the weather, while the antennas can be mounted in a location that provides clear line of sight to the sky and reduces the potential for multipath.

The SPS551 receiver provides reliable real-time GPS positioning for offshore, near shore and land-based applications including: Offshore drilling platforms, barges, ports, marine channels, and land reclamation.

The Trimble SPS551 receiver can be upgraded with GLONASS and GPS L2C signals to provide better positioning solutions in harsh GPS conditions such as areas where job site obstructions create sky visibility issues or during times of limited GPS-only availability.



<sup>1</sup> Location GPS receivers provide GPS positioning techniques including Satellite Based Augmentation Systems (SBAS), DGPS, OmniSTAR (VBS, XP and HP services), and Location RTK (decimeter-level RTK positioning) for up to decimeter-level (0.3-R) positions.



# TRIMBLE SPS551 AND SPS551H LOCATION GPS RECEIVERS

## GENERAL

Keyboard and display . . . VFD display 16 characters by 2 rows  
On/Off key for one button start up  
Escape and Enter key for menu navigation  
4 arrow keys (up, down, left, right)  
for option scrolls and data entry  
Dimensions (L x W x D) . . . . .24 cm x 12 cm x 5 cm  
(9.4 in x 4.7 in x 1.9 in)  
including connectors  
Weight . . . . . 1.65 kg (3.64 lb) receiver  
with internal battery and radio  
1.55 kg (3.42 lb) receiver  
with internal battery and no radio

## Antenna options

L1/L2/L2C GPS operation . . . GA510\* or Zephyr™ Model 2\*\*  
GLONASS operation . . . . . Zephyr Model 2\*\*  
DGPS Base Station . . . . . Zephyr Geodetic™ Model 2\*\*  
OmniSTAR operation . . . . . GA510\* or Zephyr Model 2\*\*

\* GA510 is included in the SPS551H receiver kits and provides superior OmniSTAR tracking.

\*\* Zephyr Model 2 antenna is included in the SPS551H GLN receiver kit

## Supports legacy

Trimble antennas . . . Single frequency antenna for DGPS use  
Dual frequency antenna such as Z+, Zephyr, Zephyr Geodetic, and Micro-Centered™ for heading applications

## Temperature<sup>1</sup>

Operating . . . . . -40 °C to +65 °C (-40 °F to +149 °F)  
Storage . . . . . -40 °C to +80 °C (-40 °F to +176 °F)  
Humidity . . . . . MIL-STD 810F, Method 507.4  
Waterproof . . . . . IP67 for submersion to depth of 1 m (3.3 ft), dustproof

## Shock and vibration

Designed to survive a 1 m (3.3 ft) pole drop onto a hard surface

Shock: non-operating . . . . . To 75 g, 6 ms  
Shock: operating . . . . . To 40 g, 10 ms, saw-tooth  
Vibration . . . . . Tested to Trimble ATV profile (4.5 gRMS):  
10 Hz–300 Hz: 0.04 g<sup>2</sup>/Hz;  
300 Hz–1,000 Hz; -6 dB/octave

## Measurements

- Advanced Trimble Maxwell™ 5 Custom GPS chip
- High-precision multiple correlator for L1/L2 pseudo-range measurements
- Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low time domain correlation, and high dynamic response
- Very low noise carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- L1/L2 signal-to-noise ratios reported in dB-Hz
- Proven Trimble low elevation tracking technology
- 72-channel L1 C/A code, L1/L2 Full Cycle Carrier. Upgradable to L2C and GLONASS L1/L2 Full Cycle Carrier.
- Trimble EVEREST™ multipath signal rejection
- 4-channel SBAS (WAAS/EGNOS/MSAS)

## Code differential GPS positioning<sup>2</sup>

Horizontal accuracy . . . . . 0.25 m + 1 ppm RMS  
(0.8 ft + 1 ppm RMS)  
Vertical accuracy . . . . . 0.50 m + 1 ppm RMS  
(1.6 ft + 1 ppm RMS)

## SBAS (WAAS/EGNOS/MSAS)<sup>3</sup> positioning

Horizontal accuracy . . . . . Typically <1 m (3.3 ft)  
Vertical accuracy . . . . . Typically <5 m (16.4 ft)

## OmniSTAR positioning

VBS service accuracy . . . . . Horizontal <1 m (3.3 ft)  
XP service accuracy . . . . . Horizontal 0.2 m (0.66 ft),  
Vertical 0.3 m (1.0 ft)  
HP service accuracy . . . . . Horizontal 0.1 m (0.33 ft),  
Vertical 0.15 m (0.5 ft)

## Location RTK positioning<sup>2</sup>

Horizontal accuracy . . . . . 0.07 m + 1 ppm RMS  
(0.23 ft + 1 ppm) RMS  
Vertical accuracy . . . . . 0.07 m + 1 ppm RMS  
(0.23 ft + 1 ppm) RMS

## Heading accuracy with

SPS551H or additional SPSx5x . . . . . 0.05° RMS  
(10 m antenna separation)  
Does not require shore-based corrections for heading solution

## POWER Internal

- Integrated internal battery 7.2 V, 7800 mA-hr, Lithium-ion
- Internal battery operates as a UPS in the event of external power source failure
- Internal battery will charge from external power source when input voltage is >15 V
- Integrated charging circuitry

## External

- Power input on 7-pin 0-shell Lemo connector is optimized for lead acid batteries with a cut-off threshold of 10.5 V
- Power input on the 26-pin D-sub connector is optimized for Trimble Lithium-ion battery input with a cut-off threshold of 9.5 V
- Power source supply (Internal/External) is hot-swap capable in the event of power source removal or cut off
- 9.5 V to 28 V DC external power input with over-voltage protection
- Receiver will automatically turn on when connected to external power

Power consumption . . . . . 6.0 W in rover mode  
with internal receive radio  
8.0 W in base mode  
with internal transmit radio

## Base station operation times on internal battery

External radio . . . . . 15 hours;  
varies with temperature  
Internal radio (450 MHz, 0.5 W) . . . . . 11 hours;  
varies with temperature



## Rover operation times on internal battery

450 MHz systems . . . . . 13 hours; varies with temperature  
 900 MHz systems . . . . . 13 hours; varies with temperature

## Regulatory approvals

- FCC: Part 15 Subpart B (Class B Device) and Subpart C, Part 90
- Industry Canada: ICES-003 (Class B Device), RSS-210, RSS-Gen, RSS-310, RSS-119
- R&TTE Directive: EN 301 489-1/-5/-17, EN 300 440, EN 300 328, EN 300 113, EN 60950, EN 50371
- ACMA: AS/NZS 4295 approval
- CE mark compliance;
- C-tick mark compliance
- UN ST/SG/AC.10.11/Rev. 3, Amend. 1 (Lithium-ion Battery)
- UN ST/SG/AC. 10/27/Add. 2 (Lithium-ion Battery)
- RoHS compliant (excludes those with an internal 900 MHz radio)
- WEEE compliant

## Communications

Port 1 (7 pin 05 Lemo)  
 Serial 1 . . . . . 3 wire RS232

Port 2 (26 pin D-sub)  
 Serial 2 . . . . . Full 9 wire RS-232  
 Serial 3 . . . . . 3 wire RS232  
 1PPS (pulse per second) . . . . . via adapter cable  
 USB (On the Go) . . . . . via multi-port adapter  
 Ethernet . . . . . via multi-port adapter  
 Bluetooth . . . . . Fully-integrated, fully-sealed  
 2.4 GHz Bluetooth<sup>5</sup> module

Integrated radios (optional) . . . . Fully integrated, fully sealed  
 internal 450 MHz (UHF) Tx/Rx;  
 Internal 900 MHz Tx/Rx

Channel spacing (450 MHz) . . . . .12.5 KHz or 25 KHz  
 spacing available  
 End-user configurable

450 MHz output power . . . . . 0.5 W, 2.0 W  
 (2.0 W available only  
 in certain countries)

Frequency approvals (900 MHz) . . . . . USA/Canada (-10)  
 New Zealand/Australia (-20)  
 Australia (-30)

Receiver position update rate . . . . . 1 Hz, 2 Hz, 5 Hz,  
 and 10 Hz positioning

Correction data input  
 (SPS551) . . . . . CMR, CMR+, RTCM 3, RTCM 2.x

Correction data output  
 (SPS551) . . . . . CMR/CMR+ (for Moving Baseline),  
 RTCM 2.x (DGPS only)

Data outputs . . . . . NMEA, GSOFF, 1PPS Time Tags

## Receiver options and upgrades

SPS551 GLONASS . . . . . Uses GLONASS L1/L2  
 satellite signals

450 MHz Radio 2.0 W. . . . Available only in certain countries

SPS551 L2C (upgrade only) . . . . . Uses GPS L2C  
 satellite signals

## Receiver operations capability

SPS551 . . . . . SBAS, OmniSTAR services,  
 DGPS Base or Rover,  
 Moving Base or Heading,  
 Location RTK Rover

SPS551H . . . . . Heading add-on only

1 Receiver will operate normally to -40°C. Bluetooth module and internal batteries are rated to -20°C.  
 2 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry,  
 and atmospheric conditions. Always follow recommended practices.  
 3 Depends on SBAS system performance.  
 4 If your receiver has the 2.0 W upgrade, you will experience reduced battery performance compared to  
 the 0.5 W solution.  
 5 Bluetooth type approvals are country-specific. For more information, contact your local Trimble office or  
 representative.

Specifications subject to change without notice.

© 2007, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. CMR, CMR+, Geodetic, EVEREST, HYDRopro, Maxwell, VRS, and Zephyr Geodetic are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022482-980 (09/07)



### NORTH AMERICA

Trimble Construction Division  
 5475 Kellenburger Road  
 Dayton, Ohio 45424  
 USA  
 800-538-7800 (Toll Free)  
 +1-937-245-5154 Phone  
 +1-937-233-9441 Fax

### EUROPE

Trimble GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY  
 +49-6142-2100-0 Phone  
 +49-6142-2100-550 Fax

### ASIA-PACIFIC

Trimble Navigation  
 Singapore PTE Ltd.  
 80 Marine Parade Road, #22-06  
 Parkway Parade  
 Singapore, 449269  
 SINGAPORE  
 +65 6348 2212 Phone  
 +65 6348 2232 Fax

YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE



www.trimble.com